

YH5122-1CAR



Feature

- 300.0 (L) x 101.7 (W) x 83.8 (H) mm
- 1+1 Redundant
- Support PMBus 1.2
- Application for IPC/Storage/Embedded server/Networking



INPUT	
Input Voltage	90-264VAC @1000W, 100-264VAC @1100W, 180-264VAC @1200W
Input Frequency	47-63Hz
Input Current	15A max at 115VAC, 8.0A max at 240VAC
Inrush Current	100A max at 264VAC
Power Factor	0.95 at 115VAC / 60Hz, 0.90 at 230V / 50Hz
Earth Leakage Current	3.5mA max at 240VAC / 50Hz

GENERAL	
Efficiency	80 Plus GOLD certified, Highest efficiency 92% at 230VAC
Power Density	
MTBF	100 kWhrs per Bellcore SR-332 at 25°C ambient

ENVIRONMENTAL	
Operating Temperature	0 to 50°C
Operating Humidity	85% RH, Non-condensing
Storage Temperature	-40°C to +70 °C
Operating Altitude	Sea level to 5,000 M
Shock Operating	5G, no malfunction
Non-Operating	50G, no damage
Vibration Operating	0.01G ² /Hz at 10Hz, 0.02G ² /Hz at 20Hz
Non-Operating	0.02G ² /Hz form 20Hz to 1kHz

EMC & SAFETY	
Emissions	EN55022, class A Conducted / EN55022, class A Radiated
Harmonic Currents	EN61000-3-2
Voltage Flicker	EN61000-3-3
EFT/Burst	EN61000-4-4
Surge	EN61000-4-5
Conducted Immunity	EN61000-4-6
Safety Approvals	UL/cUL, TUV, CB, CE, CCC, FCC

Output	Minimum Load	Maximum Load	Condition	Ripple & Noise
+3.3V	0.1A	24A	+3.3V ~ +5V combined power ≤ 180W	50mV p-p
+5V	0.1A	35A		50mV p-p
+12V	1.0A	75.5A @1000W 79A @1100W 82.5A @1200W		120mV p-p
-12V	0A	0.5A		120mV p-p
+5Vsb	0.1A	6.0A		50mV p-p

YH5122-1CAR

