

## YVIC0450CM-2A00N01



### Feature

- 195.0 (L) x 50.5 (W) x 39.0 (H) mm
- N+1 Redundant
- Support PMBus 1.2
- Application for IPC/Storage/Embedded server/Networking



INPUT	
Input Voltage	-36- -72VDC
Input Current	17.0A / -36VDC, 9.0A / -72VDC
Inrush Current	100A max at -72VDC
Earth Leakage Current	

GENERAL	
Efficiency	85% at Max load of -48VDC
Power Density	
MTBF	100 kHrs per Telcordia SR-332 at 25°C ambient

ENVIRONMENTAL	
Operating Temperature	0 to 50°C
Operating Humidity	85% RH, Non-condensing
Storage Temperature	-40°C to +70 °C
Operating Altitude	Sea level to 5,000 M
Shock Operating	10G, no malfunction
Non-Operating	50G Trapezoidal Wave, Velocity change 4.3m/sec
Vibration Operating	0.01G <sup>2</sup> /Hz at 10Hz, 0.02G <sup>2</sup> /Hz at 20Hz
Non-Operating	0.02G <sup>2</sup> /Hz form 20Hz to 1kHz

EMC & SAFETY	
Emissions	EN55032, class A Conducted / EN55032, class A Radiated
Harmonic Currents	N/A
Voltage Flicker	EN61000-3-3
EFT/Burst	EN61000-4-4
Surge	EN61000-4-5
Conducted Immunity	EN61000-4-6
Safety Approvals	UL/cUL, TUV, CB, CE, CCC, FCC

Output	Minimum Load	Maximum Load	Condition	Ripple & Noise
+12V	0A	37.5A		120mV p-p
+5Vsb	0A	3.0A		50mV p-p

## YVIC0450CM-2A00N01

